CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Corner established by J. Meldrum under Contract No. 139 dated 8-31-1870.

Surveyor General's Record states:

Set stone 18x15x12 for 1/4 Section Corner.


DIAGRAM



Description of corner evidence found:

Found 18x13x11" stone marked 1/4 on East side in 2-foot mound.

Description of monument and accessories I established to perpetuate the original location of this corner: Declination 20° East.



At corner position I set a 2" x 30" aluminum pipe with 3¼" cap stamped as shown 1.9 feet in soil. Stone buried adjacent to and East of monument. 3' x 0.6' rock and soil mound was raised to monument's top.

Accessories taken:

Ponderosa Pine 11" in diameter bears N85° East 31.0 feet scribed 1/4 S31 BT.
Ponderosa Pine 9" in diameter bears N60° West 34.5 feet scribed 1/4 S36 BT.

To new bearing trees a 3/4" brass washer stamped PLS-2039 was nailed into the BT blaze. USFS sign 54-4 was attached to a metal fence post 5 feet South of corner and to the back of all bearing trees.

A bearing tree tag marked with reference information was nailed above all BT blazes. A 6" red band was painted on a smoothed bark surface above all BT tags.

I hereby certify that the above corner monument was set as herein described on 7/26/1985.

William G Bahrke

Office of County Surveyor County of Crook
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 15th day of November, 1985
David B. Armstrong by
(COUNTY OFFICIAL) (DEPUTY)

WILL

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON JULY 15, 1983 WILLIAM G. BAHRKE 2039

William G Bahrke

Form R6-7100-57 (9/71)

X-25